

VSRT California Stock Steam Boiler

Model: VSRT-30-S-CA (California Special)

Fulton VSRT boilers are fully factory test fired and supplied with ASME BEP hydrostatic certifications. The VSRT provides the industry's highest efficiencies with low NOX emissions as standard. Each boiler is supplied fully trimmed and is ready to be installed.

Boiler Rating:	30 BHP
Boiler Input:	1,200 CFH
Boiler Output:	1,035 LBS/HR
Trim Pressure:	150 PSI
Gas Pressure Req.:	3-14 IN WC
Electrical Power Req.:	240/60/1 15 AMPS
Turndown:	6:1
NOx:	<20 PPM
CO:	<10 PPM

Built To Codes:

ASME Section I, CSD-1, SCAQMD, CA State Code

Fitted & BEP Tested Trim:

- Feedwater Ball and Check Valve
- Steam Stop Valve
- Manual Bottom Blowdown Valves - (1) Quick, (1) Slow
- Siemens Ventless Gas Train

Standard Boilers Fitted With:

- Dual Setpoint (Night Heat)
- Alarm Package
- Manual Surface Blowdown
- Secondary Safety Shut-Off Valve



Dimensions & Weights:

Boiler Min. Width:	60"
Rec. Clearance:	24" sides/rear, 36" front
Burner Removal Height:	110"
Operating Weight:	4,100 lbs
Flooded Weight:	4,400 lbs

Connection Sizes:

Gas Inlet:	1.25" NPT
Feedwater Inlet:	1" NPT
Bottom Blowdown:	1.25" NPT
Steam Outlet:	2" NPT
Stack:	8"