

Fulton Stock Feedwater System

Model: HT-200

Location: Fresno, California

For Boiler Sizes:	Up to 200 HP
For Boiler Trim Pressure:	150 PSI
# of Pumps:	2
Pump Setup:	One Pump Operating, One in the Backup
Pump Orientation:	Continuous Run with Recirculation
Pump Make/Model:	Grundfos CR5-14
Electrical Power Req.:	460/60/3 17 AMPS



Built To Codes:

UL-508A Control Panel

Fitted & BEP Tested Trim:

- ❑ Float Type Water Level Control
- ❑ Solenoid Makeup
- ❑ Fully Assembled Preheat Kit
- ❑ Chemical Injection Quill

Deaerator & Pump Controls:

- ❑ Fused, Panel Mounted Disconnect for Single Point Power
- ❑ Fused, External Pump Disconnects
- ❑ Low Water Cutoff and Low/High Alarms
- ❑ Auto Backup Pump Activation

Reference Drawings B91- 101234 and B53-15507

Dimensions & Weights:

Width:	90-1/4"
Length:	122-5/16"
Height:	115-3/4"
Shipping Weight:	2,523 lbs
Flooded Weight:	3,921 lbs

Connection Sizes:

Cold Water Inlet:	1" NPT
Pump Discharge (2x):	1-1/4" NPT
Steam Inlet:	2" NPT
Condensate Return:	3" NPT
Vent Outlet:	3" NPT